

## INTERIM MATERIAL SAFETY DATA SHEET FOR

TECTYL 816

PHYSICAL DATA

Values are for:

Solvent/diluent ( ) Product (x)

1. Solvent/diluent	0	%
2. Initial b.p.	>600	°F
3. <del>M.P.</del> Pour point	10	°F
4. Flash point (o.c.)	400	°F
5. Flammable limits	-	%
6. Autoignition temp.	-	°F
7. Specific gravity	0.89-0.90	
8. Water solubility	negligible	

B. HAZARD CLASSIFICATION

1. Explosive (DOT)	( )
2. Poison, Class A (DOT)	( )
3. Poison, Class B (DOT)	( )
4. Poison, Class C (DOT)	( )
5. Corrosive material (DOT)	( )
6. Oxidizing agent (DOT)	( )
7. Flammable liquid (DOT)	( )
8. Combustible liquid	( )
9. Irritant	(x)

C. ESTABLISHED TLV (ppm)

For product	For components major	minor	
( )	1. (x)	( )	500
	2. ( )	( )	
	3. ( )	( )	
	4. ( )	( )	
	5. ( )	( )	

D. PROTECTIVE EQUIPMENT

1. No protection	( )
2. Special ventilation	( )
3. Respirator	( )
4. Face shield	( )
5. Safety glasses	(x)
6. Gloves	(x)
7. Boots	( )
8. Protective suit	( )
9. Other	wear long gloves

E. FIRST-AID PROCEDURE

## EYE CONTAMINATION

1. Flush with water	(x)
2. Call a physician	( )
3. Other	

## SKIN CONTAMINATION

1. Flush with water	( )
2. Flush with soap and water	(x)
3. Flush with dilute acid	( )
4. Flush with dilute alkali	( )
5. Call a physician	( )
6. Other	

## INTERNAL CONTAMINATION

1. Drink large volume water	( )
2. Induce vomiting	( )
3. Do not induce vomiting	(x)
4. Vinegar water	( )
5. Sodium bicarbonate	( )
6. Egg whites	( )
7. Plaster	( )
8. Call a physician	(x)
9. Other	

F. FIRE FIGHTING PROCEDURE

1. Water	(x)
2. Carbon dioxide	(x)
3. Foam	(x)
4. Dry chemical	(x)
5. Carbon tetrachloride	( )
6. Other	

G. SPILL PROCEDURE

1. Eliminate ignition source	( )
2. Stop spill at source	(x)
3. Contain spill by dike, etc.	(x)
4. Cover with fire fighting foam	( )
5. Dilute with water	( )
6. Pump into salvage tank	(x)
7. Keep upwind	( )
8. Use water-spray to down vapor	( )
9. Other	

H. WASTE DISPOSAL PROCEDURE

1. Liquid incineration	(x)
2. Absorbent disposal	( )
3. Other	

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

WITH REGARD TO THE MATERIAL ASHLAND MAKES NO WARRANTY OF ANY KIND WHATEVER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY ASHLAND.

COMPLETED BY: N S Salomons / R L Harrison

DATE: April 12, 1972

TECTYL is a registered trademark of ASHLAND OIL, INC.

INTERIM MATERIAL SAFETY DATA SHEETS ENCLOSED

TECTYL 816